Table 4-2: Performance Standards for Residential Uses by District

District/ Subdivision Type	Maximum Gross Density (du/ac.)	Minimum Open Space Ratio <sup>1</sup>	
Urban Core (UC)		<del>-</del>	
Performance	See Article V, Sections 502.	02 and 506.03	
_	ricts (UN-E), (UN-W), & (UN-S)		
Conventional	4.00	0.00	
Performance	See Article V, Sections 502.	02., 506.04., and 509.	
Neighborhood Conservatio			
	See Article V, Table 5-2		
Development District Hous	sing (DD-H)		
Conventional	4.00	0.00	
Performance	5.50	0.30	
Medium Density Residentic	al District (MDRD)		
Performance	12.00	0.15	
Neighborhood Redevelopm	nent District (NRD)		
Conventional	5.50	0.00	
Performance	8.00	0.20	
Redevelopment District (R	DD)		
Conventional	5.00	0.00	
Performance	16.00	0.20	
Rural (R)			
Conventional	3 acre min. lot size	0.00	
Limited Development Distr	rict (LDD)		
Conventional	2.00	0.00	
Performance	5.00	0.30	
Comprehensive Developme	ent (CDD)		
Conventional	4.00	0.00	
Performance	9.50	0.25	
Corridor Redevelopment D	District (CPD II)		
Performance	16.00	0.15	
Corridor Redevelopment D Performance	District (CRD-E) 10.00	0.15	
		0.13	
Corridor Redevelopment D		0.00	
Performance	10.00	0.20	
Corridor Redevelopment D	District (CRD-W)		
Performance	10.00	0.20	

<sup>&</sup>lt;sup>1</sup>No open space shall be required in a performance residential development consisting of 4 dwelling units or less on an existing lot of record. No open space shall be required for town houses constructed in the Urban Core (UC), all Urban Neighborhood (UN-E) (UN-W) & (UN-S), and Corridor Redevelopment District-Urban (CRD-U) districts.

See Article V, Section 503